

marking hose designed for waterblasting equipment. A more ecologically friendly alternative to sandblasting and other abradant cleaning and stripping methods, waterblasting puts a significant level of stress on hose — inside and out. CRP Pressure Cleaning hose is of the highest quality and available with quick couplers already installed. What's more, our fast

• Smooth, non-abrasive coverings for challenging working conditions

PRESSURE WASHER SERIES

WIRE REINFORCED PRESSURE CLEANING HOSE



Multi-purpose hose that can be used for heavy duty pressure cleaning jobs. Reinforced with braided steel wire. Medium to high oil resistance.

CONSTRUCTION:

Inner: Modified Nitrile

Outer: Synthetic Rubber RMA Class B

COUPLING CAPABILITIES:	NIDT NIDOM IIC DISE	od or Stainlass Staal	M or E
COUPLING CAPABILITIES:	NP1. NPSM. JIC Plat	ed or Stainiess Steel – <i>i</i>	vi or F

CRP PART NUMBER	COLORS	# OF BRAIDS	NOMINAL I.D. Inches (MM)	NOMINAL O.D. Inches (MM)	MINIMUM BEND RADIUS Inches (MM)	DYNAMIC WORKING PRESSURE	MAXIMUM BURST PRESSURE	MAXIMUM WEIGHT (LBS/FT)	LENGTH	TEMPERATURE RANGE
PC1		1	3/8 (9.5)	0.69 (17.5)	N/A	3,000 psi	12,000 psi	0.24	150′	-20 to +250°F*
PC2		2	3/8 (9.5)	0.69 (17.5)	N/A	4,500 psi	18,000 psi	0.36	50'	-20 to +250°F*
PCN		1	3/8 (9.5)	0.69 (17.5)	N/A	3,000 psi	12,000 psi	0.24	50'	-20 to +250°F*

CRP also carries all the hose accessories you need. See pages 46-60 for details.





