



Butyl Crush Resistant



INDUSTRIES

8110 Series




Premium food and beverage hose featuring low permeation. This hose features synthetic plies that allow the hose to rebound

Technical Characteristics:

Temperature Range:	-40°C /+100 °C (-40°F/+212 °F)
Dimensional Tolerance:	ISO1307
Vacuum:	0.7 bar (10 psi)

Hose Construction:

- Tube:** Bromobutyl (BIIR), white, phthalates free, complies with 1907/2006/CE (REACH), FDA 21 CFR 177.2600, DM21.03.73 e seguenti, European Reglement 1935/2004/CE, 3A Sanitary Standard Class II
- Reinforcement:** Plies of Synthetic Cord; Embedded synthetic helix Wires.
- Cover:** Low friction material, red color. Wide Corrugated, glossy finish; Abrasion, Ozone and Weather resistant.
- Color Options:** 
- Sterilization:** See cleaning and sterilizing guidelines for food and beverage hose.

Inside Diameter		Outside Diameter		Vacuum		Working Pressure		Burst Pressure		Weight		Bend Radius	
mm	in	mm	in	bar	psi	bar	psi	bar	psi	kg/m	lbs/ft	mm	in
38	1.5	55	2.13	0.7	10	10	150	30	450	1.45	0.97	170	6.69
51	2	68	2.64	0.7	10	10	150	30	450	1.84	1.23	240	9.44
63.5	2.5	81.5	3.21	0.7	10	10	150	30	450	2.48	1.66	310	12.2
76	3	94	3.7	0.7	10	10	150	30	450	2.9	1.94	380	14.96

www.crpindustrial.com