

Stainless Steel True-Bore PTFE/FEP Hose

CRP Industrial is your go-to source for true-bore, smooth-bore stainless steel hose with PTFE or FEP tubes. CRP's Reinflex brand offers a comprehensive line-up to meet the needs for a variety of applications. Complete assemblies or cut lengths are available with a multitude of fittings to choose from.

Stainless Braided PTFE Hose						
CRP Part No.	Inside Diameter	Working Pressure	Burst Pressure	Temperature Range		
103K	1/8"	3,260 PSI	13,040 PSI	-65°F to 450°F		
105K	3/16"	3,000 PSI	12,000 PSI	-65°F to 450°F		
106K	1/4"	3,000 PSI	12,000 PSI	-65°F to 450°F		
110K	3/8"	2,000 PSI	8,000 PSI	-65°F to 450°F		
113K	1/2"	1,750 PSI	7,000 PSI	-65°F to 450°F		
120K	3/4"	1,000 PSI	4,000 PSI	-65°F to 450°F		



Stainless 2-Wire Braided PTFE Hose							
CRP Part No.	Inside Diameter	Working Pressure	Burst Pressure	Temperature Range			
206K	1/4"	3,990 PSI	15,950 PSI	-65°F to 450°F			
210K	3/8"	3,260 PSI	13,050 PSI	-65°F to 450°F			
213K	1/2"	2,900 PSI	11,600 PSI	-65°F to 450°F			
220K	3/4"	2,180 PSI	8,700 PSI	-65°F to 450°F			
225K	1"	1,810 PSI	7,540 PSI	-65°F to 450°F			



Polyurethane Covered FEP Hose						
CRP Part No.	Inside Diameter	Working Pressure	Burst Pressure	Temperature Range		
206ST	1/4"	6,162 PSI	24,650 PSI	-40°F to 176°F		
210ST	3/8"	5,000 PSI	20,000 PSI	-40°F to 176°F		
213ST	1/2"	4,710 PSI	18,850 PSI	-40°F to 176°F		
220ST	3/4"	3,840 PSI	15,230 PSI	-40°F to 176°F		
225ST	1"	3,262 PSI	13,050 PSI	-40°F to 176°F		





To speak to a CRP representative today, contact **800.526.4066** or **industrialcs@crpindustries.com**