



Backed by OE quality, Reinflex's Sewer Jetting Hoses meet the requirements for all sewer equipment. It is ideal for high pressure applications in even the most harsh sewer environments. Lightweight fabric or steel wire reinforced, our sewer jetting hose is available in many standard stocking assemblies, allowing us to drop ship anywhere quickly. For those requiring hose in long lengths, we are also able to provide speedy turnaround. In addition, we can design custom fittings and fabrications based on your application needs, and of course, no job is too big or too small.

SEWER JETTING HOSE FEATURES:

- Working pressures from low to very high (6,170 psi)
- Fitting options — NPT, NPSM, and JIC in plated or Stainless Steel – male (M) or female (F)
- Lengths from 4" up to 600'
- Hose sizes (ID) from 1/8" to 1/2"
- Provides excellent abrasion and fungus resistance
- Meets Waste Equipment Technology Association (WETA) specifications

is for Sewer Jetting



1000SJ SERIES

FABRIC BRAID REINFORCED THERMOPLASTIC SEWER JETTING HOSE



Sewer Line Jetting Hose with high tensile fabric braid reinforcement. Provides excellent abrasion, cut, and fungus resistance. Meets Waste Equipment Technology Association specifications.

CONSTRUCTION:

Inner: Yellow Olefin Tube


Outer: Abrasion and Chemical Resistant Polyurethane Cover

COUPLING CAPABILITIES: NPT, NPSM, JIC Plated or Stainless Steel – M or F

CRP PART NUMBER	COLORS	# OF BRAIDS	NOMINAL I.D. Inches (MM)	NOMINAL O.D. Inches (MM)	MINIMUM BEND RADIUS Inches (MM)	DYNAMIC WORKING PRESSURE	MINIMUM BURST PRESSURE	WEIGHT (LBS/FT)	MAXIMUM LENGTH	TEMPERATURE RANGE
1003SJ	■	2	1/8 (3.2)	0.32 (8.1)	1.3 (32)	4,000 psi	10,000 psi	0.04	4" up to 600'	-40 to +150°F
1004SJ	■	2	3/16 (4.8)	0.41 (10.4)	1.8 (45)	4,000 psi	10,000 psi	0.05	4" up to 600'	-40 to +150°F
1006SJ	■	2	1/4 (6.4)	0.50 (12.7)	2.5 (64)	4,000 psi	10,000 psi	0.06	4" up to 600'	-40 to +150°F
1010SJ	■	2	3/8 (9.5)	0.65 (16.5)	3.0 (76)	4,000 psi	10,000 psi	0.11	4" up to 600'	-40 to +150°F
1013SJ	■	2	1/2 (12.7)	0.83 (21.1)	4.0 (102)	4,000 psi	10,000 psi	0.16	4" up to 600'	-40 to +150°F

1000AV SERIES

FABRIC BRAID REINFORCED THERMOPLASTIC SEWER JETTING HOSE



A high pressure semi-conductive thermoplastic hose that will not swell or degrade when in contact with most chemicals, oils, and solvents. Extremely durable. Ideal for where electrostatic charge must be dissipated and high temperature applications.

CONSTRUCTION:

Inner: Seamless Nylon Liner

Outer: Abrasion and Chemical Resistant Polyurethane Cover

COUPLING CAPABILITIES: NPT, NPSM, JIC Plated or Stainless Steel – M or F

CRP PART NUMBER	COLORS	# OF BRAIDS	NOMINAL I.D. Inches (MM)	NOMINAL O.D. Inches (MM)	MINIMUM BEND RADIUS Inches (MM)	DYNAMIC WORKING PRESSURE	MINIMUM BURST PRESSURE	WEIGHT (LBS/FT)	MAXIMUM LENGTH	TEMPERATURE RANGE
1003AV	■	1	1/8 (3.2)	0.32 (8.1)	1.3 (32)	3,500 psi	14,000 psi	0.03	4" up to 500'	0 to 180°F
1004AV	■	2	3/16 (4.8)	0.43 (10.9)	1.8 (45)	3,500 psi	14,000 psi	0.05	4" up to 500'	0 to 180°F
1006AV	■	2	1/4 (6.4)	0.49 (12.5)	2.5 (64)	3,300 psi	13,200 psi	0.05	4" up to 500'	0 to 180°F
1010AV	■	2	3/8 (9.5)	0.72 (18.2)	3.0 (76)	3,300 psi	13,200 psi	0.11	4" up to 500'	0 to 180°F

1000UK SERIES

WIRE REINFORCED THERMOPLASTIC SEWER JETTING HOSE



A high pressure, high performance hose with steel braid reinforcement for strength and guaranteed electrical conductivity. Offers optimum resistance to a wide range of chlorinated solvents, and other chemicals. Extremely durable. Cover is pin-pricked standard.

CONSTRUCTION:

Inner: Seamless Nylon Liner

Outer: Abrasion and Chemical Resistant Polyurethane Cover

COUPLING CAPABILITIES: NPT, NPSM, JIC Plated or Stainless Steel – M or F

CRP PART NUMBER	COLORS	# OF BRAIDS	NOMINAL I.D. Inches (MM)	NOMINAL O.D. Inches (MM)	MINIMUM BEND RADIUS Inches (MM)	DYNAMIC WORKING PRESSURE	MINIMUM BURST PRESSURE	WEIGHT (LBS/FT)	MAXIMUM LENGTH	TEMPERATURE RANGE
1003K	■	1	1/8 (3.2)	0.27 (7.0)	1.2 (30)	5,075 psi	20,300 psi	0.04	4" up to 500'	-40 to +212°F
1004UK	■ ■	1	3/16 (4.8)	0.37 (9.4)	1.0 (25)	5,250 psi	21,000 psi	0.08	4" up to 500'	-40 to +212°F
1006UK	■ ■	1	1/4 (6.4)	0.46 (11.7)	1.5 (37)	5,000 psi	18,000 psi	0.11	4" up to 500'	-40 to +212°F
1010UK	■ ■	1	3/8 (9.5)	0.60 (15.1)	2.0 (50)	3,500 psi	13,000 psi	0.15	4" up to 500'	-40 to +212°F
1013UK	■ ■	1	1/2 (12.7)	0.72 (18.3)	3.0 (75)	3,000 psi	12,000 psi	0.20	4" up to 500'	-40 to +212°F

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.

TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

2000UK SERIES

WIRE REINFORCED THERMOPLASTIC SEWER JETTING HOSE



A high pressure, high performance Sewer Jetting Hose with steel braid reinforcement for strength and guaranteed electrical conductivity. Offers optimum resistance to a wide range of paints, chlorinated solvents, and other chemicals. Extremely durable. Cover is pin-pricked standard.

CONSTRUCTION:

Inner: Seamless Nylon 6 Liner = 2006/2010/2013
Seamless Nylon 12 Liner = 2020/2025

Outer: Abrasion and Chemical Resistant Polyurethane Cover

COUPLING CAPABILITIES: NPT, NPSM, JIC Plated or Stainless Steel – M or F

CRP PART NUMBER	COLORS	# OF BRAIDS	NOMINAL I.D. Inches (MM)	NOMINAL O.D. Inches (MM)	MINIMUM BEND RADIUS Inches (MM)	DYNAMIC WORKING PRESSURE	MINIMUM BURST PRESSURE	WEIGHT (LBS/FT)	MAXIMUM LENGTH	TEMPERATURE RANGE
2006UK	■	2	1/4 (6.4)	0.54 (13.7)	1.0 (25)	6,170 psi	28,000 psi	0.21	4" up to 500'	-40 to +212°F
2010UK	■ ■	2	3/8 (9.5)	0.67 (17.0)	1.5 (37)	6,000 psi	22,000 psi	0.28	4" up to 500'	-40 to +212°F
2013UK	■ ■	2	1/2 (12.7)	0.80 (20.2)	2.5 (62)	5,000 psi	17,000 psi	0.34	4" up to 300'	-40 to +212°F
2020UK	■	2	3/4 (19.1)	1.07 (27.1)	6.7 (170)	3,100 psi	13,000 psi	0.50	4" up to 300'	-40 to +212°F
2025UK	■	3**	1 (25.4)	1.46 (37.1)	10.0 (254)	4,750 psi	19,000 psi	0.61	4" up to 300'	-40 to +212°F*

*+158°F for water based fluids

**Wire and kevlar reinforced



CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.

TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.